


Product data sheet

IMS CONNECTOR SYSTEMS GmbH
 Obere Hauptstrasse 30
 D-79843 Löffingen
 Postfach 1141
 D-79840 Löffingen

Tel (+49) 7654 901-0
 Fax (+49) 7654 901-199
 Net: www.imscs.com
 E-mail: sales@imscs.com

Part Number: 1690.09.1420.061 Description: MMCX(m)-Angle plug		Revision: c Date: 1999.06.12 Signature: Schwär Page: 1 of 2																																																	
Design according to:		DIN EN 122340 (Type MMCX)																																																	
Electrical characteristics:		<div style="background-color: #e0ffe0; padding: 2px; font-size: small;">colored value means: still under test target value</div> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 60%;">Value</th> <th style="width: 15%;">Unit</th> <th style="width: 25%;">Picture</th> </tr> </thead> <tbody> <tr> <td>Impedance (MIL-C- 39012B)</td> <td>50</td> <td>[Ω]</td> </tr> <tr> <td>Operating frequency up to</td> <td>..6</td> <td>[GHz]</td> </tr> <tr> <td>Return loss measured with cable typ:</td> <td>UT 85</td> <td>-</td> </tr> <tr> <td> 1 GHz</td> <td>35</td> <td>[dB]</td> </tr> <tr> <td> 2 GHz</td> <td>26</td> <td>[dB]</td> </tr> <tr> <td> 4 GHz</td> <td>17</td> <td>[dB]</td> </tr> <tr> <td> 6 GHz</td> <td>16</td> <td>[dB]</td> </tr> <tr> <td>3rd. Order PIM product 2x43dBm</td> <td>/</td> <td>[dBc]</td> </tr> <tr> <td>Insulation resistance</td> <td>≥ 1</td> <td>[GΩ]</td> </tr> <tr> <td>Contact resistance</td> <td></td> <td></td> </tr> <tr> <td> Centre contact</td> <td>≤ 5</td> <td>[mΩ]</td> </tr> <tr> <td> Outer contact</td> <td>≤ 2,5</td> <td>[mΩ]</td> </tr> <tr> <td>Contact current max. (DC)</td> <td>max. 1,2</td> <td>[A]</td> </tr> <tr> <td>Operating voltage</td> <td>170</td> <td>[V]</td> </tr> <tr> <td>Proof voltage</td> <td>500</td> <td>[V]</td> </tr> </tbody> </table>		Value	Unit	Picture	Impedance (MIL-C- 39012B)	50	[Ω]	Operating frequency up to	..6	[GHz]	Return loss measured with cable typ:	UT 85	-	1 GHz	35	[dB]	2 GHz	26	[dB]	4 GHz	17	[dB]	6 GHz	16	[dB]	3rd. Order PIM product 2x43dBm	/	[dBc]	Insulation resistance	≥ 1	[GΩ]	Contact resistance			Centre contact	≤ 5	[mΩ]	Outer contact	≤ 2,5	[mΩ]	Contact current max. (DC)	max. 1,2	[A]	Operating voltage	170	[V]	Proof voltage	500	[V]
Value	Unit	Picture																																																	
Impedance (MIL-C- 39012B)	50	[Ω]																																																	
Operating frequency up to	..6	[GHz]																																																	
Return loss measured with cable typ:	UT 85	-																																																	
1 GHz	35	[dB]																																																	
2 GHz	26	[dB]																																																	
4 GHz	17	[dB]																																																	
6 GHz	16	[dB]																																																	
3rd. Order PIM product 2x43dBm	/	[dBc]																																																	
Insulation resistance	≥ 1	[GΩ]																																																	
Contact resistance																																																			
Centre contact	≤ 5	[mΩ]																																																	
Outer contact	≤ 2,5	[mΩ]																																																	
Contact current max. (DC)	max. 1,2	[A]																																																	
Operating voltage	170	[V]																																																	
Proof voltage	500	[V]																																																	
																																																			
		Remarks at 910MHz / at 1870 MHz																																																	
Mechanical characteristics:		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 60%;">Value</th> <th style="width: 15%;">Unit</th> <th style="width: 25%;">Remarks</th> </tr> </thead> <tbody> <tr> <td>Engagement force</td> <td>6 -12</td> <td>[N]</td> </tr> <tr> <td>Separating force</td> <td>6 -15</td> <td>[N]</td> </tr> <tr> <td>Mating cycles</td> <td>min. 500</td> <td></td> </tr> </tbody> </table>		Value	Unit	Remarks	Engagement force	6 -12	[N]	Separating force	6 -15	[N]	Mating cycles	min. 500																																					
Value	Unit	Remarks																																																	
Engagement force	6 -12	[N]																																																	
Separating force	6 -15	[N]																																																	
Mating cycles	min. 500																																																		

Product data sheet

IMS CONNECTOR SYSTEMS GmbH
 Obere Hauptstrasse 30
 D-79843 Löffingen
 Postfach 1141
 D-79840 Löffingen

Tel (+49) 7654 901-0
 Fax (+49) 7654 901-199
 Net: www.imscs.com
 E-mail: sales@imscs.com

Part Number: 1690.09.1420.061	Revision: c
Description: MMCX(m)-Angle plug	Date: 1999.06.12
	Signature: Schwär
	Page: 2 of 2

<u>Material & plating:</u>	RoHS (2002/95/EC) conform	
	Material	Plating
Housing	Brass	Cu + Ni + 0,8µm Au
Contact pin	Brass	Cu + Ni + 1,3µm Au
Insulator	PTFE	-
Clip	Copper beryllium	Cu + Ni + 0,8µm Au
Other metal parts	Brass	Cu + Ni + 0,2µm Au

<u>Environmental influences:</u>		Remarks
Operating temperature range	-65°C up to +165°C Standard	
Climatic sequence: 1. Dry heat 2. Damp heat, cyclic, 1 cycle 3. Cold 4. Damp heat, cyclic, 6 cycles	IEC 60068-2-61 IEC 60068-2-2-Ba IEC 60068-2-30-Db IEC 60068-2-1-Aa IEC 60068-2-30-Db	
Solder profile:	-	

Notes:

<u>Update historie</u>			
Rev.	Date	Alteration	Signature
a	1999.07.29	revised	Schwär
b	2000.01.26	revised	Schwär
c	2011.05.05	revised	Pölz