


Product Data Sheet / Produkt Datenblatt

Part Number	309.23.2415.481	Teilenummer
Description	Cable mount jack	Beschreibung
		
Design according to	Coax inserts for D-sub Connectors	Ausführung nach

Electrical characteristics / Elektrische Eigenschaften

		colored value means: under validation		
		Value/Wert	Unit/Einheit	
Impedance (MIL-C-39012B)		50	[Ω]	Impedanz (MIL-C-39012B)
Operating frequency up to		1	[GHz]	Betriebsfrequenz bis zu
Return loss				Rückflusdämpfung
measured with cable type: RG-58	1 GHz	> 12	[dB]	gemessen mit Kabeltyp: RG-58
Insulation resistance		1	[GΩ]	Isolationswiderstand
Contact resistance				Kontakt-Widerstand
Centre contact		≤ 6	[mΩ]	Innenkontakt
Outer contact		≤ 3	[mΩ]	Außenkontakt
Contact current max. (DC)		1,5	[A] DC	Kontakt-Strombelastbarkeit max (DC)
Operating voltage		≥ 250	[VRMS]	Betriebsspannung
Proof voltage		750	[VRMS]	Prüfspannung

Mechanical characteristics / Mechanische Eigenschaften

		Value/ Wert	Unit/Einheit	
Engagment force		max. 10	[N]	Steckkraft
Separating force		min. 2	[N]	Ziehkraft
Mating cycles		> 500		Steckzyklen

Product Data Sheet / Produkt Datenblatt

Part Number	309.23.2415.481	Teilenummer
Description	Cable mount jack	Beschreibung

Material & plating / Material & Oberfläche

RoHS (2002/95/EC) conform			
	Material/Material	Plating/Oberflächen	
Connecting piece	Brass	Cu + Ni + 0,2µm Au	Anschlussstück
Main part	Brass	Ni + 0,8µm Au	Hauptstück
Contact socket	Copper beryllium	Ni + 1,3µm Au	Innenbuchse
Ferrule	Brass	Cu + Ni + 0,2µm Au	Hülse
Clipping	Brass	Cu + 3-5µm Ni	Haltering
Insulator	PTFE	-	Isolierung

Environmental influences / Umwelteinflüsse

Operating temperature range	-55°C up to +125°C	Betriebstemperaturbereich
	Standard	
Climatic sequence:	IEC 60068-2-61	Klimafolge:
1. Dry heat	IEC 60068-2-2-Ba	1. Trockene Hitze
2. Damp heat, cyclic, 1 cycle	IEC 60068-2-30-Db	2. Feuchte Wärme, zyklisch, 1 Zyklus
3. Cold	IEC 60068-2-1-Aa	3. Kälte
4. Damp heat, cyclic, 6 cycles	IEC 60068-2-30-Dd	4. Feuchte Wärme, zyklisch, 6 Zyklen
Solder profile		Lötprofil

Notes / Aufzeichnungen

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Update History

Rev.	Date	Signature	Alteration
			Formblatt-Nr.: Form-TK-013b
			Rev. 04
			Released 17.04.14