

# Product data sheet

IMS CONNECTOR SYSTEMS GmbH  
 Obere Hauptstrasse 30  
 D-79843 Löffingen  
 Postfach 1141  
 D-79840 Löffingen

Tel (+49) 7654 901-0  
 Fax (+49) 7654 901-199  
 Net: www.imscs.com  
 E-mail: sales@imscs.com

<b>Part Number: 4023.42.1610.003</b> <b>Description: SMA-p.c.b. mount plug rev.pol.</b>		<b>Revision: a</b> <b>Date: 08.11.2005</b> <b>Signature: U. Mayer</b> <b>Page: 1 of 2</b>																																																					
<b>Design according to:</b>	<b>SMA Reverse Polarity</b>	<b>No IEC Standard</b>																																																					
<b>Electrical characteristics:</b>	<small>colored value means: still under test target value</small>																																																						
	<table border="1"> <thead> <tr> <th>Value</th> <th>Unit</th> <th>Picture</th> </tr> </thead> <tbody> <tr> <td>Impedance ( MIL-C- 39012B)</td> <td><b>50</b></td> <td>[Ω]</td> </tr> <tr> <td>Operating frequency up to</td> <td><b>10</b></td> <td>[GHz]</td> </tr> <tr> <td>Return loss measured with cable typ:</td> <td>-</td> <td>-</td> </tr> <tr> <td>    1 GHz</td> <td><b>37</b></td> <td>[dB]</td> </tr> <tr> <td>    2 GHz</td> <td><b>35</b></td> <td>[dB]</td> </tr> <tr> <td>    4 GHz</td> <td><b>33</b></td> <td>[dB]</td> </tr> <tr> <td>    6 GHz</td> <td><b>31</b></td> <td>[dB]</td> </tr> <tr> <td>    10 GHz</td> <td><b>15</b></td> <td>[dB]</td> </tr> <tr> <td>    18 GHz</td> <td>-</td> <td>[dB]</td> </tr> <tr> <td>3rd. Order PIM product 2x43dBm</td> <td>/</td> <td>[dBc]</td> </tr> <tr> <td>Insulation resistance</td> <td><b>5</b></td> <td>[GΩ]</td> </tr> <tr> <td>Contact resistance</td> <td></td> <td></td> </tr> <tr> <td>    Centre contact</td> <td><b>3,0</b></td> <td>[mΩ]</td> </tr> <tr> <td>    Outer contact</td> <td><b>2,0</b></td> <td>[mΩ]</td> </tr> <tr> <td>Contact current max. (DC)</td> <td><b>2</b></td> <td>[A]</td> </tr> <tr> <td>Operating voltage</td> <td><b>500</b></td> <td>[V]</td> </tr> <tr> <td>Proof voltage</td> <td><b>1000</b></td> <td>[V]</td> </tr> </tbody> </table>	Value	Unit	Picture	Impedance ( MIL-C- 39012B)	<b>50</b>	[Ω]	Operating frequency up to	<b>10</b>	[GHz]	Return loss measured with cable typ:	-	-	1 GHz	<b>37</b>	[dB]	2 GHz	<b>35</b>	[dB]	4 GHz	<b>33</b>	[dB]	6 GHz	<b>31</b>	[dB]	10 GHz	<b>15</b>	[dB]	18 GHz	-	[dB]	3rd. Order PIM product 2x43dBm	/	[dBc]	Insulation resistance	<b>5</b>	[GΩ]	Contact resistance			Centre contact	<b>3,0</b>	[mΩ]	Outer contact	<b>2,0</b>	[mΩ]	Contact current max. (DC)	<b>2</b>	[A]	Operating voltage	<b>500</b>	[V]	Proof voltage	<b>1000</b>	[V]
Value	Unit	Picture																																																					
Impedance ( MIL-C- 39012B)	<b>50</b>	[Ω]																																																					
Operating frequency up to	<b>10</b>	[GHz]																																																					
Return loss measured with cable typ:	-	-																																																					
1 GHz	<b>37</b>	[dB]																																																					
2 GHz	<b>35</b>	[dB]																																																					
4 GHz	<b>33</b>	[dB]																																																					
6 GHz	<b>31</b>	[dB]																																																					
10 GHz	<b>15</b>	[dB]																																																					
18 GHz	-	[dB]																																																					
3rd. Order PIM product 2x43dBm	/	[dBc]																																																					
Insulation resistance	<b>5</b>	[GΩ]																																																					
Contact resistance																																																							
Centre contact	<b>3,0</b>	[mΩ]																																																					
Outer contact	<b>2,0</b>	[mΩ]																																																					
Contact current max. (DC)	<b>2</b>	[A]																																																					
Operating voltage	<b>500</b>	[V]																																																					
Proof voltage	<b>1000</b>	[V]																																																					
		<b>Remarks</b> at 910MHz / at 1870 MHz																																																					
<b>Mechanical characteristics:</b>	<table border="1"> <thead> <tr> <th>Value</th> <th>Unit</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td>Engagement force</td> <td>-</td> <td>[N]</td> </tr> <tr> <td>Separating force</td> <td>-</td> <td>[N]</td> </tr> <tr> <td>Mating cycles</td> <td><b>&gt; 500</b></td> <td></td> </tr> </tbody> </table>	Value	Unit	Remarks	Engagement force	-	[N]	Separating force	-	[N]	Mating cycles	<b>&gt; 500</b>																																											
Value	Unit	Remarks																																																					
Engagement force	-	[N]																																																					
Separating force	-	[N]																																																					
Mating cycles	<b>&gt; 500</b>																																																						

