

Product Data Sheet / Produkt Datenblatt Seite 1 / 2

Part Number	7472.PSMP.1014.195	Teilenummer
Description	PSMP Bulkhead Plug (customise interface similar to smooth bore)	Beschreibung
		
Design according to	PSMP (customise interface similar to smooth bore)	Ausführung nach

Electrical characteristics / Elektrische Eigenschaften

		colored value means: still under test target value		
		Value/Wert	Unit/Einheit	
Impedance (MIL-C-39012B)		50	[Ω]	Impedanz (MIL-C-39012B)
Operating frequency up to		18	[GHz]	Betriebsfrequenz bis zu
Return loss				Rückflussdämpfung
	DC to 2 GHz	≥39	[dB]	
	2 to 4 GHz	≥39	[dB]	
	4 to 6 GHz	≥39	[dB]	
	6 to 10 GHz	≥26	[dB]	
	10 to 18 GHz	≥18	[dB]	
Insertion loss		≤0.03x√f[GHz]	[dB]	
Statisch 3rd. order PIM	at 1870MHz,2x43dBm	160	[dBc]	PIM Produkt 3. Ordnung
Insulation resistance		≥5	[GΩ]	Isolationswiderstand
Contact resistance				Kontakt-Widerstand
Centre contact		≤3	[mΩ]	Innenkontakt
Outer contact		≤2	[mΩ]	Außenkontakt
Power handling (at 20°C, sea level, VSWR1.0)	at 2.2GHz	≤200	[W]	
Operating voltage		480	[V] eff	Betriebsspannung
Proof voltage		1000	[V] eff	Prüfspannung

Mechanical characteristics / Mechanische Eigenschaften

		Value/ Wert	Unit/Einheit	
Mating cycles				
if mating part is limited detent		≥100		
Center contact captivation		≥7	[N]	
Engagement force				
smooth bore		≤10	[N]	
Disengagement force				
smooth bore		≥2.2	[N]	

Product Data Sheet / Produkt Datenblatt Seite 2 / 2

Part Number	7472.PSMP.1014.195	Teilenummer
Description	PSMP Bulkhead Plug (customise interface similar to smooth bore)	Beschreibung

Material & plating / Material & Oberfläche

	RoHS (2002/95/EC) conform		
	Material/Material	Plating/Oberflächen	
Outer contact	Brass	Cu +min. 2µm Ag +min.0,5µm CuZnSn	Außenkontakt
Centre contact	Brass	Ni-P + 0,15µm Au	Innenkontakt
Crimp ferrule	-	-	Crimphülse
Other metal parts	-	-	sonstige Metallteile
Insulator	PTFE	-	Isolator
Gasket	-	-	Dichtung

Environmental influences: Umwelteinflüsse

Operating temperature range	-55°C up to +125°C Standard	Betriebstemperaturbereich
Climatic sequence:	IEC 60068-2-61	Klimafolge:
1. Dry heat	IEC 60068-2-2-Ba	1. Trockene Hitze
2. Damp heat, cyclic, 1 cycle	IEC 60068-2-30-Db	feuchte Wärme, zyklisch, 1 Zyklus
3. Cold	IEC 60068-2-1-Aa	3. Kälte
4. Damp heat, cyclic, 6 cycles	IEC 60068-2-30-Db	feuchte Wärme, zyklisch, 6 Zyklen
Solder profile		Lötprofil

Notes: Aufzeichnungen

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Update History

Rev.	Date	Signature	Alteration
A	2018.12.11	Dony	mod. RL

Formblatt-Nr.: Form-TK-013b	
Rev.	04
Released	17-Apr-14