


**Product Data Sheet / Produkt Datenblatt**

<b>Part Number</b>	<b>5220.VDZ.2018.205</b>	<b>Teilenummer</b>
<b>Description</b>	<b>4.3-10 - Flanschbuchse 4.3-10 - Flange mount jack</b>	<b>Beschreibung</b>
		
<b>Design according to</b>	<b>IEC-61169-54</b>	<b>Ausführung nach</b>

**Electrical characteristics / Elektrische Eigenschaften**

		colored value means: under validation		
		Value/Wert	Unit/Einheit	
Impedance (MIL-C-39012B)		50	[Ω]	Impedanz (MIL-C-39012B)
Operating frequency up to		....10	[GHz]	Betriebsfrequenz bis zu
Return loss	measured with cable typ:			gemessen mit Kabel Typ: Rückflusdämpfung
	1 GHz	>40	[dB]	
	2 GHz	>40	[dB]	
	4 GHz	33	[dB]	
	6 GHz	28	[dB]	
	10 GHz	21	[dB]	
3rd. Order PIM product 2x43dBm	at 1870MHz	<168	[dBc]	PIM Produkt 3. Ordnung
Insulation resistance		5	[GΩ]	Isolationswiderstand
Contact resistance				Kontakt-Widerstand
	Centre contact	1,0	[mΩ]	Innenkontakt
	Outer contact	0,25	[mΩ]	Außenkontakt
Contact current max. (DC)		4,0	[A] DC	Kontakt-Strombelastbarkeit max (DC)
Operating voltage		500	[V] DC	Betriebsspannung
Proof voltage		1000	[V] eff	Prüfspannung

**Mechanical characteristics / Mechanische Eigenschaften**

		Value/ Wert	Unit/Einheit	
Mating cycles		> 100		Steckzyklen
Centre contact retention force		30	[N]	Haltekraft Innenleiter
Centre contact detent torque		3	[Ncm]	Haltemoment Innenleiter
Recommended coupling torque		5	[Nm]	Empfohlenes Anzugsmoment

**Product Data Sheet / Produkt Datenblatt**

<b>Part Number</b>	<b>5220.VDZ.2018.205</b>	<b>Teilenummer</b>
<b>Description</b>	<b>4.3-10 - Flanschbuchse 4.3-10 - Flange mount jack</b>	<b>Beschreibung</b>

**Material & plating / Material & Oberfläche**

RoHS (2002/95/EC) conform			
	Material/Material	Plating/Oberflächen	
Outer contact	Copper beryllium	min. 3µm Cu + 3-6µm Ag	Außenkontakt
Centre contact	Copper beryllium	min. 3µm Cu + 3-6µm Ag	Innenkontakt
Housing	Brass	Cu + 2-4µm CuZnSn	Gehäuse
Nut	Brass	Cu + 2-4µm CuZnSn	
Insulator	PTFE	-	Isolator
Gasket	Silicone/Silikon	-	

**Environmental influences / Umwelteinflüsse**

Operating temperature range	-55°C up to +90°C Standard	Betriebstemperaturbereich
Thermal shock	IEC 60169-1, Sub-clause 16.4	Thermischer Schock
Corrosion resistance	ISO 21207 method B	Korrosionsbeständig
Vibration	IEC 61169-1 9.3.3 and IEC 60068-2-64	Vibration
Shock	IEC 61169-1 9.3.14	Schock
Degree of protection (mated pair)	IEC 60529, IP68 1h / 25m	Schutzart (gesteckte Paarung)

**Notes / Aufzeichnungen**

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

**Update History**

Rev.	Date	Signature	Alteration
			Formblatt-Nr.: Form-TK-013b
			Rev. 04
			Released 17. Apr 14