

Product Data Sheet / Produkt Datenblatt

Part Number	5285.VDZ.2010.195	Teilenummer
Description	4.3/10 (m) - Bulkhead plug 4.3/10 (m) - Chassisstecker	Beschreibung
		
Design according to	IEC-61169-54	Ausführung nach

Electrical characteristics / Elektrische Eigenschaften

		colored value means: under validation		
		Value/Wert	Unit/Einheit	
Impedance (MIL-C-39012B)		50	[Ω]	Impedanz (MIL-C-39012B)
Operating frequency up to		6	[GHz]	Betriebsfrequenz bis zu
Return loss				Rückflusdämpfung
	1 GHz	> 36	[dB]	
	3 GHz	> 32	[dB]	
	4 GHz	> 28	[dB]	
	6 GHz	> 26	[dB]	
Power levels at 40°C ambient temp.	2 GHz	250	[W]	Leistung bei 40°C Umgebungstemp.
	6 GHz	100	[W]	
3rd. Order PIM product 2x20 W	at 2 GHz	≥ 165	[dBc]	PIM Produkt 3. Ordnung 2x20 W
Insulation resistance		> 5	[GΩ]	Isolationswiderstand
Contact resistance				Kontakt-Widerstand
Centre contact		≤ 1,0	[mΩ]	Innenkontakt
Outer contact		≤ 0,25	[mΩ]	Außenkontakt
Contact current max. (DC)		4	[A] DC	Kontakt-Strombelastbarkeit max (DC)
Operating voltage		≥ 500	[VRMS]	Betriebsspannung
Proof voltage		1000	[VRMS]	Prüfspannung

Mechanical characteristics / Mechanische Eigenschaften

		Value/ Wert	Unit/Einheit	
Mating cycles		≥ 100		Steckzyklen
Centre contact captivation: axial		> 70	[N]	Innenleiter Arretierung: axial
Isolation captivation: axial		> 70	[N]	Isolation Arretierung: axial
Recommended coupling torque		5	[Nm]	Empfohlenes Anzugsmoment

Product Data Sheet / Produkt Datenblatt

Part Number	5285.VDZ.2010.195	Teilenummer
Description	4.3/10 (m) - Bulkhead plug 4.3/10 (m) - Chassisstecker	Beschreibung

Material & plating / Material & Oberfläche

	RoHS (2002/95/EC) conform		
	Material/Material	Plating/Oberflächen	
Housing	Brass	min. 3 CuSnZn	Gehäuse
Centre contact	Copper beryllium	min. 2 µm Cu + min. 5 µm Ag	Innenkontakt
Spring basket	Bronze	min. 2 µm Cu + min. 5 µm Ag	Federkorb
Insulator	PTFE	-	Isolator

Environmental influences / Umwelteinflüsse

Operating temperature range	-55°C up to +125°C	Betriebstemperaturbereich
	Standard	
Climatic sequence:	IEC 60068-2-61	Klimafolge:
1. Dry heat	IEC 60068-2-2-Ba	1. Trockene Hitze
2. Damp heat, cyclic, 1 cycle	IEC 60068-2-30-Db	2. Feuchte Wärme, zyklisch, 1 Zyklus
3. Cold	IEC 60068-2-1-Aa	3. Kälte
4. Damp heat, cyclic, 6 cycles	IEC 60068-2-30-Dd	4. Feuchte Wärme, zyklisch, 6 Zyklen

Notes / Aufzeichnungen

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Update History

Rev.	Date	Signature	Alteration		
a	2016.01.13	Fabiankovits	updated		
b	2017.01.10	Fabiankovits	power levles		
c	2017.08.02	Fabiankovits	material list		
				Formblatt-Nr.: Form-TK-013b	
				Rev.	04
				Released	17.04.14