

IMS Product Specification/ Product Data Sheet

Part Number	5562.NEX.1410.085	Teilenummer
Description	NEX10(m)-Kabelstecker NEX10(m)-Cable mount plug	Beschreibung
		

Design according to **RT-NEX10** **Ausführung nach**

Electrical characteristics / Elektrische Eigenschaften

		colored value means: under validation			
		Value/Wert	Unit/ Einheit		
Impedance (MIL-C-39012B)		50	[Ω]	Impedanz (MIL-C-39012B)	
Operating frequency up to		...20	[GHz]	Betriebsfrequenz bis zu	
Return loss	measured with cable typ: RFS SCF14-50J			gemessen mit Kabel Typ: Rückflussdämpfung	
	@ DC to 4 GHz	≥26	[dB]		
	@ 4 to 6 GHz	≥23	[dB]		
	@ 6 to 10 GHz	≥20	[dB]		
	@ 10 to 20 GHz	≥15	[dB]		
Insertion loss		≤0.05 x √f[GHz]	[dB]		
RF-leakage	@ DC to 6 GHz	≥110	[dB]		
3rd. Order PIM product 2x43dBm	at 910MHz/at 1870MHz	≥165	[dBc]	PIM Produkt 3. Ordnung	
Insulation resistance		≥5	[GΩ]	Isolationswiderstand	
Contact resistance				Kontakt-Widerstand	
Centre contact		≤1.5	[mΩ]	Innenkontakt	
Outer contact		≤1.5	[mΩ]	Außenkontakt	
Power handling	at 2GHz and 85°C	100	[W] DC	Belastbarkeit	
	at 2GHz and 105°C	50	[W] DC		
Working voltage	max.	500	[V] eff	Spannung	
Test voltage	min.	1500	[V] eff	Prüfspannung	

Mechanical characteristics / Mechanische Eigenschaften

		Value/ Wert	Unit/ Einheit		
Mating cycles		≥100		Steckzyklen	
Retention force of coupling mecha.		>500	[N]	Haltekraft für Kupplungsmechanismus	
Recommended torque		1,5	[Nm]	Empfohlenes Anzugsmoment	
Water resistance	(mated pair)	IP68 24h/1m		Wasserbeständigkeit (gestecktes Paar)	

Date/Generated: 16.09.2019 R. Schwär Revision a
 Date/Approved: 12.03.2020 P. Schuh

IMS Product Specification/ Product Data Sheet

Part Number	5562.NEX.1410.085	Teilenummer
Description	NEX10(m)-Kabelstecker NEX10(m)-Cable mount plug	Beschreibung

Material & plating / Material & Oberfläche

RoHS (2011/65/EU) conform			
	Material/Material	Plating/Oberflächen	
Outer contact	Copper beryllium	Cu + 5-8µm Ag	Außenkontakt
Centre contact	Brass	Cu + 5-8µm Ag	Innenkontakt
Housing	Brass	Cu + 2-4µm CuZnSn	Gehäuse
Nut	Brass	Cu + 2-4µm CuZnSn	Mutter
Spring ring	Stainless steel	-	Federring
Insulator	PTFE	-	Isolator
Gasket	Silicone/Silikon	-	Dichtung

Environmental influences / Umwelteinflüsse

Operating temperature range	-55°C up to +125°C	Betriebstemperaturbereich
Thermal shock	IEC 61169-1 9.4.4.	Wärme Schock
Vibration	IEC 61169-1 9.3.3 and IEC 60068-2-64	Vibration
Shock	IEC 61169-1 9.3.14	Schock
RoHS	compliant	
Solder profile		Lötprofil

Notes / Aufzeichnungen

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Date/Generated: 16.09.2019 R. Schwär

Revision

a

Date/Approved: 12.03.2020 P. Schuh